

Removing and installing centre console (front)

1 - Centre console (front)

◆ Removing

- Remove centre console (rear)
→ **Chapter**.
- Open ashtray (front) and unclip trim section -2- at retaining clips -3- (6x) ("chorus and concert" radios only).
- Remove radio, vehicles with "chorus and concert" radio
→ **Rep. Gr.91**.
- Remove radio, vehicles with "symphony" radio → **Rep. Gr.91**.
- Remove operating electronics control unit with radio/navigation system plus
→ **Rep. Gr.91**.
- Removing air conditioner control panel/heater controls
→ **Rep. Gr.87**
- Remove ashtray (front) on vehicles with "chorus and concert" radio → **Chapter**.
- Remove ashtray (front) on vehicles with "symphony" radio and "radio/navigation system plus" → **Chapter**.
- Unclip switch module trim -5- at retaining clips -4- (4x).
- Unscrew bolts -6- (4x).
- Prise out trim -7-.
- Remove nut -8-.
- Pull centre console on driver's side over securing pin.
- Pull out centre console towards rear.

◆ Installing

- When inserting centre console -1-, fit retainer -9- in retaining clip.

2 - Trim section

3 - Retaining clip

4 - Retaining clip

5 - Trim for switch module

6 - Bolts (4x)

- Tightening torque: 5 Nm

7 - Trim

8 - Nut

9 - Retaining bracket

